





GP DC Miniature Diaphragm Pump

Quality OEM Electric Diaphragm Pump Series D

>> Brush Motor



>> Brushless DC Motor



>> Diaphragm Selection

| Material | Performance |
|----------|--|
| EPDM | Good resistance to alcohols, acids, bases, oxidants, ketones, and esters; poor oil resistance. |
| HNBA | Excellent oil resistance, corrosion resistance, ozone resistance, alcohol resistance, low-temperature resistance, and high-temperature resistance. (Poor resistance to alcohols, esters, and aromatic refrigerants.) |
| FKM | Non-stick, high polarity, corrosion-resistant; shorter lifespan compared to EPDM. |
| FFKM | Temperature range from -10°C to 230°C; excellent resistance to aggressive chemicals, including acids, bases, solvents, fuels, and steam. Suitable for highly reactive substances. |

>> DC Motor

| Model Number | Air Version | | | | Liquid Version | | | |
|--------------|-------------|-------------------|----------|-------|----------------|-----------------|--------------|-------|
| | Pressure | Negative Pressure | Air Flow | Power | Flow Rate | No-load Current | Load Current | Power |
| 90/6V | 0.04MPA | -0.03MPA | 2LPM | 1.5W | 90ml/min | 0.15A | 0.26A | 1.56W |
| 90/12V | 0.04MPA | -0.03MPA | 1LPM | 1.5W | 90ml/min | 0.15A | 0.26A | 1.56W |
| 160/6V | 0.045MPA | -0.038MPA | 2LPM | 2.5W | 160ml/min | 0.18A | 0.32A | 2W |
| 160/12V | 0.045MPA | -0.04MPA | 2LPM | 2W | 160ml/min | 0.18A | 0.32A | 2W |
| 160/24V | 0.058MPA | -0.04MPA | 3LPM | 2W | 160ml/min | 0.18A | 0.32A | 2W |
| 220/6V | 0.058MPA | -0.045MPA | 2.5LPM | 2.5W | 220ml/min | 0.11A | 0.14A | 1.68W |
| 220/12V | 0.058MPA | -0.045MPA | 3LPM | 2.5W | 220ml/min | 0.11A | 0.14A | 2.4W |

>> BLDC Motor

| Motor Number | Air Version | | | | Liquid Version | | | |
|--------------|-------------|-------------------|----------|-------|----------------|--------------|-------|-------------|
| | Pressure | Negative Pressure | Air Flow | Power | Flow Rate | Load Current | Power | Noise Level |
| BLDC/6V | 0.07MPA | -0.043MPA | 1.3LPM | 1.2W | 200ml/min | 0.35A | 2W | ≤55dBA |
| BLDC/12V | 0.07MPA | -0.043MPA | 1.3LPM | 1.58W | 200ml/min | 0.2A | 2.5W | ≤55dBA |
| BLDC/24V | 0.07MPA | -0.043MPA | 1.3LPM | 1.68W | 200ml/min | 0.12A | 3W | ≤55dBA |